

## Short Form Classification Report No. 22059D

### PRODUCT

Clearline PV16-series

### SPONSOR

VIRIDIAN SOLAR LIMITED

### PRODUCT DETAILS

#### Integrated solar panel

- Range of panels: see annex A
- Thickness: 70/69 mm
- Weight: 27,5 kg / 25,0 kg / 23,5 kg / 21,7 kg / 21,4 kg
- Dimensions: 1903 x 1134 mm / 1722 x 1134 mm / 1762 x 1039 mm / 1686 x 1000 mm / 1640 x 992 mm
- Mechanically fixed

### FIELD OF APPLICATION

- Range of pitches:  $\geq 20$
- Range of substrates: Supporting structure (as tested)
- Full extended field of application: see annex A

### CLASSIFICATION

Broof(T1)

### STANDARDS

Test standard: CEN/TS 1187:2012

Classification standard: EN 13501-5:2016

SIGNED

APPROVED

*For and on behalf of WFRGENT nv*

This short form classification report has been drafted according to EGOLF agreement EGA 039:2021 "Application note: clause 7.8 [7.8/1] – Types of reports". It has not been drafted under the requirements of EN ISO/IEC 17025 accreditation and is not valid to officially classify a product. The full classification report No. **22059C** is available at **VIRIDIAN SOLAR LIMITED**.

This document is the original version of this report and is written in English. This document may be used only literally and completely for publications. For publications of certain texts, in which this document is mentioned, our permission must be obtained in advance. The authenticity of the electronic signatures is assured by Belgium Root CA.

## Annex A: Extended field of application

### ➤ Layer 0: Integrated solar panel

Range of panels:	Clearline PV16-260P-B/W, Clearline PV16-270, Clearline PV16-270P-B/W, Clearline PV16-280 and Clearline PV16-300, Clearline PV16-320, Clearline PV16-325, Clearline PV16-330, Clearline PV16-335, Clearline PV16-340, Clearline PV16-345, Clearline PV16-350, Clearline PV16-355, , Clearline PV16-360, Clearline PV16-365, Clearline PV16-370, Clearline PV16-375, Clearline PV16-380, Clearline PV16-385, Clearline PV16-390, Clearline PV16-395, Clearline PV16-400, Clearline PV16-405, Clearline PV16-410, Clearline PV16-415, Clearline PV16-425, Clearline PV16-430, Clearline PV16-435, Clearline PV16-440, Clearline PV16-445, Clearline PV16-450, Clearline PV16-455 and Clearline PV16-460
Facing:	Low-iron glass
Backing	PV Backsheet (Black and white)
Thickness:	70/69 mm
Weight of 1 solar panel:	27,5 kg / 25,0 kg / 23,5 kg / 21,7 kg / 21,4 kg
Dimensions:	1903 x 1134 mm / 1722 x 1134 mm / 1762 x 1039 mm / 1686 x 1000 mm / 1640 x 992 mm
Direction:	Portrait or landscape
Fixation:	Mechanically fixed and installed with the respective flashings including Fusion Portrait Flashing Kits, Fusion Landscape Flashing Kits and Fusion Flashing Kits for Sarking Boards

### ➤ Layer 1: Non-combustible roof tiles and slates

Range of products:	Any non-combustible tile or slate (A1 according to EN 13501-1)
--------------------	--

### ➤ Layer 2: Wooden battens

Dimensions:	25 x 50 mm
Density:	450 kg/m <sup>3</sup>

### ➤ Layer 3: Unidek Aero 6 insulating panel

Material:	EPS with a timber backing
Thickness:	209 mm
Surface weight:	20,2 kg/m <sup>2</sup>

### ➤ Layer 4: Supporting timbers

Dimensions:	47 x 70 mm
Density:	450 kg/m <sup>3</sup>